Cascade Fountains
A Division of Fountain Design Group, Inc.


7628 NW 6th Avenue
Boca Raton, FL 33487

800-446-1537
www.cascadefountains.com

ARIES 1000

10 HP | THREE-TIER FLOATING FOUNTAIN

The Aries 1000 creates a dramatic three-tier water display featuring a 30-foot clear vertical center stream, surrounded by outward-arching tiers reaching 20 and 12 feet. Six 36-watt white LED lights accent the fountain after dark.



THREE-TIER DISPLAY
30' CENTER
20' SECOND
12' THIRD



SPECIFICATIONS

Water Display	Three-tier spray pattern
Center Tier	30' clear vertical stream
Second Tier	20' outward-arching jets
Third Tier	12' outward-arching jets
Motor Power	10 HP
Electrical Service	460/480 VAC, three-phase
Rated Load	14 FLA (3-phase panel)
Lighting	(6) 36W white LED lights
Minimum Water Depth	6 feet
Flotation Unit	6' rotocast, four-chamber
Warranty	3 years

INSTALLATION & ELECTRICAL

Dedicated electrical supply and installation by qualified personnel required. Field conductor, circuit protection and installation must comply with applicable codes and approved equipment documentation.

STANDARD EQUIPMENT

- 6-foot rotocast flotation unit with four watertight, anti-drumming chambers
- 10 HP pump and motor assembly
- Franklin or Grundfos motor and pump wet end, depending on configuration
- Three-tier spray assembly with clear vertical center stream and arching jet tiers
- (6) 36-watt white LED lighting fixtures
- 250-foot electrical power cable
- Mooring equipment included
- UL listed industrial control panel in a NEMA 3R enclosure, 20" W x 24" H x 8" D **

CONTROL PANEL - UL LISTED

UL listed industrial control panel with NEMA 3R enclosure and ground-fault protection. Supply: 460/480 VAC, three-phase service and a transformed 460/480 VAC service to 115/120 VAC. Total load on panel: **.

** This control panel will require two separate disconnects. Please contact the factory.